



## Mortar Tub Top Lift Basic

A 250 Litre Capacity Mortar Tub suitable for moving Mortar around a site.

Rigid, strong, durable, and made from high quality polyethylene.

Rigidity under load is achieved by radius and roll formed corners.

- Top Lift Tubs can be lifted on a pallet or by the rim
- Tub can be filled to the curve top
- Method of lifting by the rim will depend on the size of the forks
- Capacity of the tub is 250 litres
- SWL is 500 KG
- Do not overfill the tub if it is to be lifted by the rim
- Filling the tub to two thirds of the capacity when lifting by the rim can increase the longevity and maintain the integrity of the tub
- The tub should only be lifted by a trained and certified FLT driver, following standard procedures

Issue No 1  
01/05/2022

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

### NEWBURY

**01635 876336**  
[sales@ockwells.co.uk](mailto:sales@ockwells.co.uk)

### WARRINGTON

**01925 820003**  
[sales.warrington@ockwells.co.uk](mailto:sales.warrington@ockwells.co.uk)

### GLASGOW

**0141 427 3366**  
[sales.glasgow@ockwells.co.uk](mailto:sales.glasgow@ockwells.co.uk)

### EAST LONDON

**020 7473 8770**  
[sales.eastlondon@ockwells.co.uk](mailto:sales.eastlondon@ockwells.co.uk)