



Ockwells Standard & FR Vented Sheet

Strong, air permeable sheeting suitable for all scaffold systems and temporary perimeter fencing.

PRODUCT	Flame retardant	Colour	Weight EN 695 gsm	Tensile strength BS 7955 N/50mm	Fastening strength BS 7955 Newtons	Conforms to	Temperature range °C	Air permeability	Aerodynamic coefficient EN ISO 9237 Cf	Size metres	Roll weight kg	Pallet quantity
FLAME RETARDANT GRADES												
Flame Retardant Vented Sheeting	 BS 476 Part 12C	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39
NON-FLAME RETARDANT GRADE												
Vented Sheeting	NA	White	100	MD >630 XD >630	>500	BS 7955	-40 to +70	Windbreak 89% EN ISO 9237	NT	1.8 x 45	9.5	39

Fastening ties: Elasticated Toggle Ties
BS 7955 Pass break strength 500 N (28cm reach)

Flexo printing: maximum print area 1070 x 730mm;
repeats at 1270mm; up to 2 colours; subject to minimum quantities
Wide format digital printing: any size, no minimum quantity

Ockwells are a division of SIG Trading Ltd. SIG Trading Ltd terms and conditions of sale apply to all transactions. A copy can be provided on request and will be incorporated into the contract of sale.

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice.

NEWBURY 01635 876336 sales@ockwells.co.uk	WARRINGTON 01925 820003 sales.warrington@ockwells.co.uk	GLASGOW 0141 427 3366 sales.glasgow@ockwells.co.uk	EAST LONDON 020 7473 8770 sales.eastlondon@ockwells.co.uk
---	---	--	---